



Sleeved Can Dieline: 8.4oz / 250mL Can

Company Name:


Design/Item Name:

UPC: We only require the barcode number. All barcodes are generated by the printer for the print process

IMPORTANT INFORMATION:

- Shrink film is a clear material and requires a layer of white opaque ink to prevent the aluminum can from showing through the artwork.
- If you intend to have the aluminum can show through the artwork, creating a metallic effect, please indicate desired "knockouts" within the white layer.
- Please place your artwork within the designated "ARTWORK" layer.
- Neither fold lines or seams should go through a main panel.
- Graphics placed on fold lines will have a light fold line running through them.
- Please indicate if there is material available for color matching (ie. previously produced sleeved/printed/labelled cans)
- Some levels of shrink distortion should be expected. Please consider fold lines and distortion areas as indicated within the "Dieline" layer.
- PMS (Pantone) colors are recommended in vector art where ever possible to avoid flexographic printing registrations issues.
- For all other information regarding artwork specifications, please refer to our "Artwork Guidelines - Sleeved" file. Don't hesitate to reach out to our Creative and Preproduction team with any questions or concerns.

NOTE: It is the customers' responsibility to ensure that all new artwork abides by the relevant packaging and artwork regulations. CanCraft recommends that the customer have all new artworks approved by their governing body prior to artwork submission. Failure to do so may result in additional costs and increased lead times.




2 mm clear area (no ink)

LOW DISTORTION AREA (GRAPHICS OKAY / NO COPY)

3
M
M
B
L
E
E
D
A
R
E
A
N
O
C
O
P
Y

**0.0625" clearance
around UPC is advised**



Standard UPC size


UNDERWRAP DISTORTION (GRAPHICS OKAY / NO COPY)

2 mm clear area (no ink)

LOW DISTORTION AREA (GRAPHICS OKAY / NO COPY)

**3
M
M
B
L
E
E
D
A
R
E
A
N
O
C
O
P
Y**

**0.0625" clearance
around UPC is advised**



Standard UPC size

UNDERWRAP DISTORTION (GRAPHICS OKAY / NO COPY)